

SP-22V

Semi-automatic Case Erector and Sealer



The SP-22V semi-automatic case erector and sealer closes the bottom four flaps of a corrugated case and seals it with tape. In one continuous motion, the operator squares a case and places it on the pack table (closing the minor bottom flaps). Then, the case is pushed to the side belts where the major flaps are automatically closed. Lastly, the pressure sensitive tape is applied from the bottom tape head.

SP-22V

Semi-automatic Case Erector and Sealer

Features:

- Heavy Duty Welded Frame
- Durable Powder Coat Paint
- Crank Operated Adjustment for the Width of the Box
- Small Footprint
- Adjustable Table Height
- Sam Packaging 2" Taping Head

Options:

- Compression Rollers
- Extra Width
- 3" Tape Heads
- High Speed Motors
- Casters
- Reverse Direction

Machine Dimensions:

Length: 80"
Width: 42"
Height: 40"

Carton Dimensions:

Length: 6" to 24"
Width: 6" to 20"
Height: 4" minimum

For undersized/oversized and special cases please contact Sam Packaging LLC.

Technical Features:

Speed: Up to 15 cases per minute
Side belts speed: 60 ft/min (optional 90ft/min)
Electric Power: 110 VAC, 1Ph, 60Hz., 5.6 Amp.
Weight: 450 lbs

Sam Packaging LLC
5535 W 110th St. Unit 9
Oak Lawn IL, 60453
Tel. (708) 229-7655
Fax (844) 229-7644
www.sampackaging.com
sales@sampackaging.com